



2-Channel Solder- and Desoldering Station, 200 W (255 W)

Item No: WXD2020N

2-Channel Solder- and Desoldering Station, 200 W (255 W)

KEY FEATURES

- + Soldering and desoldering station WXD 2, 2 channels with WXDP 120 and soldering iron WXP 120
- + Soldering- and desoldering tools with intelligent WX technology
- + Connection to external compressed air supply required
- + Energy effective: automatic stand-by mode for tools
- + Patented, ESD safe glass display. Simple and fast setting of soldering parameter.
- + Standby and auto off modes for energy savings
- + Peripheral control of WHP 1000 / WHP 3000 hot plates and Zero Smog 4V and 6V fume extraction units

TECHNICAL DATA

| | |
|--|--|
| Dimensions L x W x H | 174.0 x 154.0 x 135.0mm |
| Air Consumption | 35 l/min |
| Air Pressure | 58 - 87 psi |
| Compressed Air Connection (Outer Diameter) | 0.23 in |
| Compressed Air Connection Accessory | Oil free, dry compressed air |
| Desoldering | Yes |
| Equipotential Bonding Socket | Via 3.5mm Pawl Socket on Back of Device |
| ESD Safe | Yes |
| Fuse | T2A |
| Interface | 1x USB, 2x RS232, 1x Switching Output |
| Maximum Volume | 0.7 bar |
| Number of Channels | 2 |
| Operating Pressure | 4 - 6 bar 54 - 87 psi |
| Power | 200 W (255 W) |
| Temperature Accuracy °C | ± 9 °C |
| Temperature Accuracy °F | ±9 °C |
| Temperature Range (Depends on Tool) | 199 - 849°F |
| Temperature Range °C | 93 - 454 °C |
| Temperature Range °F | 199 - 849 °F |
| Temperature Stability °C | ±2 °C |
| Temperature Stability °F | ±2 °C |
| Tip Type | WX |
| UPC | 037103305275 |
| USB | USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types |
| Vacuum | 0.5 bar (55 kPa) (8 psi) |