



## **2-Channel Hot-Air Station, 200 W (255 W)**

Item No: WXA2010N

2-Channel Hot-Air Station, 200 W  
(255 W)

### **KEY FEATURES**

- + Power unit, 2 channels with hot air iron WXHAP 200
- + Best set for hot air tasks
- + Simultaneous operation of 2 soldering tools
- + For operation with external compressed air

## TECHNICAL DATA

Dimensions L x W x H	174.0 x 154.0 x 135.0mm
Air Consumption	20 l/min
Capacity (l/min)	20 l/min
Compressed Air Connection (Outer Diameter)	0.23 in
Compressed Air Connection Accessory	Oil free, dry compressed air
Equipotential Bonding Socket	Via 3.5mm Pawl Socket on Back of Device
ESD Safe	Yes
Fuse	T2A
Hot Air (picto)	Yes
Interface	1x USB, 2x RS232, 1x Switching Output
Maximum Hot Air Flow Rate l/min (Depends on Tool)	15 l/min
Number of Channels	2
Operating Pressure	4 - 6 bar 54 - 87 psi
Power	200 W (255 W)
Temperature Accuracy °C	± 9 °C
Temperature Accuracy °F	±9 °C
Temperature Accuracy for Hot Air	±30 °C
Temperature Range °C	93 - 537 °C
Temperature Range °F	199 - 998 °F
Temperature Stability °C	±2 °C
Temperature Stability °F	±2 °C
Tip Type	WX
UPC	037103304247
USB	USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types
Voltage	110 V